

EXOV2 Hybrid Coating

PRODUCT DESCRIPTION:

EXOV2 UDHC is a cutting edge coating offering sensational dirt repellency, gloss, and durability. EXOV2 is a hybrid of a chemically bonding hard inorganic base coat and a slick wet looking and highly dirt and water repellent organic top coat. Recommended use on all painted surfaces including clear coat or matt finishes, enamel, single stage paint, wheels, chrome, or stainless parts and trim. With a remarkable 115 degree contact angles it creates water sheeting action and prevent water spotting on pitched panel surfaces. EXOV2 remains ultra-hydrophobic, glossy, and slick to the touch after more than a year of regular washing and sun exposure and makes vehicle cleaning significantly easier.



OTHER EQUIPMENT/PRODUCTS RECOMMENDED FOR USE:

- Clean, high quality microfiber towels
- Blue microfiber applicator pads
- C1 Liquid Crystal, C4 Trim Restore and C5 Wheel Armor as a base layers

PRIOR TO USE:

- All surfaces should be prepped with Panel Wipe if EXOV2 is to be used as a stand alone coating.
- C1, C4 and C5 should be given recommended cure time if EXOV2 is being used as a top coat. See individual product sheets for cure times.

RECOMMENDED USE:

- Use in place of your standard paint sealant for unmatched durability.
- Apply 2-3 coats for best results.
- Can be applied to most exterior surfaces of the vehicle.

APPLICATION INSTRUCTIONS:

-PAINT: When applying EXOV2, it is important to notice how quickly the product flashes. Because of this, you will want to work in sections no larger than 12-18 inch squares, especially if you have little or no prior experience with EXOV2. Make sure that the microfiber applicator and a clean microfiber towel are close at hand at all times. Place a small amount of product on the microfiber pad, only about 4-5 drops will do. Gently spread the EXO evenly across the 12-18 inch square you are working on, and quickly come back across the section with the clean microfiber towel. You can overlap a section that you have already done with no issues. Repeat this process around the entire car and swap the part of the microfiber you are using about every 2-3 panels. For best results, wait about 20 minutes and apply a second coat. The second coat will go on much easier. **NOTE:** If you see a section while you are working that has started to flash, increase the speed but not the pressure of your hand while wiping that area. The friction will help break down the excess product.

-GLASS: Follow instructions above, but before the vehicle is driven, outside to make sure there are no streaks or high spots. While you can put EXOV2 on all the side windows, it is not recommended for the front window or rear window if there is a wiper blade. For the best hydrophobic qualities on glass, use G1 ClearVision Glass Coating.

-PLASTIC/RUBBER/RIMS: Follow Instructions above.

A NOTE ABOUT THE HYDROPHOBIC QUALITIES OF EXOV2: Once EXO is on the paint of a vehicle, there is no need for continued maintenance aside from basic washes. The hydrophobic quality of EXOV2 is so great that if you try to use a spray wax or quick detailer, it will end up streaking. The EXOV2 will not allow other products to bond or lay down flat. For quick touch ups, you can use a diluted spray wax or quick detailer, but dilute it about 10:1 with distilled water. The product should only act as a lubricant for minor debris, not a level of protection.