

# Pad Application Guide - Lake Country Mfg. Products

	OEM & Cured Paint	Fresh Paint												
STEP 3	Ultra Finishing		PAINT SEALANT / WAX											
	Final Finishing		POLISH / SEALANT											
	Swirls, Hazes		MACHINE GLAZE											
STEP 2	Very Fine Scratches	*Finer Than 2000 Grit Abrasives	POLISH											
			COMPOUND / POLISH											
	Fine Scratches Light Oxidation	*2000 Grit Abrasives	LIGHT DUTY COMPOUND											
			HEAVY DUTY COMPOUND											
			COMPOUND / POLISH											
			LIGHT DUTY COMPOUND / POLISH											
			LIGHT DUTY COMPOUND											
			LIGHT DUTY COMPOUND											
	Medium Scratches Medium Oxidation Dust Nibs Water Spots	*1500 grit Abrasives	HEAVY DUTY COMPOUND											
			HEAVY DUTY COMPOUND											
HEAVY DUTY COMPOUND														
Deep Scratches Heavy Oxidation Paint Runs, orange Peel & Acid Rain	*1200 Grit Abrasives	HEAVY DUTY COMPOUND												
		HEAVY DUTY COMPOUND												
			<b>PAD AGGRESSION SCALE</b> ← MOST → LEAST											
<b>How to use this guide:</b> 1) Determine paint type; Fresh or OEM & Cured 2) Choose surface defect and corresponding compound / polish / sealant 3) Follow path to recommended pads			4-PLY TWISTED WOOL	50/50 WOOL/ACRYLIC	YELLOW WOOL/ACRYLIC SINGLE-PLY WOOL/ACRYLIC	FOAMED WOOL ELECTRIFIED SHEEPSKIN	PREWASHED LAMBSWOOL	PURPLE FOAM YELLOW FOAM	ORANGE FOAM	GREEN FOAM	WHITE FOAM	BLACK FOAM	BLUE FOAM RED FOAM	GOLD FOAM

\* Variations in compounds and polishes may produce different results.